Call Crest Technical Support for assistance at: 1-800-328-8908 www.cresthealthcare.com ©2016 Crest Healthcare Supply







410373C

## **Patient Stations, Crest Replacement** for Faraday® System

P/N 410374C 410373C

## **Specifications**

**ELECTRICAL** 

**Voltage Rating:** 

**MECHANICAL** 

**Connector: Wire Termination:** 

Mounting:

SIZE MEASUREMENTS

24 VAC input

Screw

Fits on standard single gang back box

Plate:

4.5" x 2.75" (Single Gang) 4.5" x 4.562" (Dual Gang)

## **Typical Installation**


1. Review designations on the Main Terminal: 1, 2, 3, B and C.

Helpful hint: Mark all conductors before removing the station being replaced.

- 2. Note these designations on the circuit board of Crest Replacement Station.
- 3. Screw wires from the Nurse Call terminals to the Crest Replacement Station.
- 4. Cap any unused wires.
- 5. Always test the nurse call station for correct operation (including cord out) before placing into service.
- 6. Extend actuator fully when not in use.

## **Circuit Board Terminal Descriptions:**

C	24 V
1	To Light (Annunciator)
2	To Light (Corridor)
3	To Light (Zone)
В	Sounder/Buzzer



Front of Receptacle