

P.O. Box 727, 195 Third Street Dassel, Minnesota 55325-0727

For Technical Assistance Call Toll-Free U.S. & Canada

1-800-328-8908

Technicians On Duty

©2005 Crest Healthcare Supply

B-39087

B-39087

7932LC Pullcord Station for Edwards Lifeline

INSTALLATION INSTRUCTIONS





CREST
HEALTHCARE SUPPLY®

P.O. Box 727, 195 Third Street Dassel, Minnesota 55325-0727

For Technical Assistance Call Toll-Free U.S. & Canada

1-800-328-8908

Technicians On Duty

7932LC Pullcord Station for Edwards Lifeline

INSTALLATION INSTRUCTIONS





©2005 Crest Healthcare Supply

SPECIFICATIONS

ELECTRICAL

Current and Voltage Rating: Resistive load 1.5 amp @ 28 VDC

0.50 amp @ 115 VAC.

Lamp: 28 Volt .04 Amp: incandescent type


MECHANICAL

Clips and rotor material: Brass, silver plated.

Index Life: 25,000 cycles minimum.

Index Angle: Spring return and positive, 30 degrees

SCHEMATIC



SPECIFICATIONS

ELECTRICAL

Current and Voltage Rating: Resistive load 1.5 amp @ 28 VDC

0.50 amp @ 115 VAC.

Lamp: 28 Volt .04 Amp: incandescent type


MECHANICAL

Clips and rotor material: Brass, silver plated.

Index Life: 25,000 cycles minimum.

Index Angle: Spring return and positive, 30 degrees

SCHEMATIC



TYPICAL HOOK-UP

Wire colors on position/finction correspond to original station terminals.

POSITION FUNCTION TABLE

Color	Orange	Violet	Grey	Red	Yellow	White	Blue
Original Terminal designation	4	5	2	3	7	6	1
Up position	X	X	X				Х
Middle position	X			Х	X	X	Х
Down position (momentary)	X			X	X	X	X
Green wire is ground							

TYPICAL HOOK-UP

Wire colors on position/finction correspond to original station terminals.

POSITION FUNCTION TABLE

Color	Orange	Violet	Grey	Red	Yellow	White	Blue		
Original Terminal designation	4	5	2	3	7	6	1		
Up position	X	X	X				X		
Middle position	X			Х	X	X	X		
Down position (momentary)	X			X	X	X	X		
Green wire is ground									