

### Features

- Call type is indicated by one of four colored LEDs.
- A call tone sounds for the highest priority call.
- UL/cUL®1069 and UL®2560 Listed.
- RoHS Compliant.

### Description

The SF125 Duty Station annunciates calls both audibly and visually via 4 colored LEDs and a tone speaker. The various call priorities will be indicated by the LEDs and the highest level call will be annunciated by time. Watched zones are programmable via the LS450 Config Tool.

The SF125 Duty Station connects via the LI122 Room Controller with Dome Light or the PM120 Room Controller, using 2 of the 6 connection points. Each NC120 or NC160 Central Equipment Module supports up to 24 duty stations (6 duty stations per run) depending on power restrictions. Refer to the Tek-CARE® [Master Station Load Value Calculator](#) on TekTone's website for more information on power restrictions.

The station's plastic bezel snaps onto the included mounting plate, leaving no visible screw holes.

### Listings



UL® 1069, UL® 2560, and cUL® listed to CSA C22.2 No. 205; UL® File Number E71599.



RoHS Compliant.



SF125 Duty Stations

### Specifications

- Dimensions: 4.58"H × 6.74"W × 1.03"D  
(116 mm × 171 mm × 26 mm)
- Environment: 5%–95% non-condensing humidity;  
0°C–60°C
- Construction: PC board with quality electronic components mounted on a flame-retardant (UL® 94V-0) plastic faceplate.
- Mounting: Attach included back plate to a standard single- or double-gang ring, or single- or double-gang ring and box.
- Connections: 2-wire flying lead, a plus 2 screw terminals for the toner module. Uses 2 of the station module's 6 points.

### Required Components

NC120 or 160 Central Equipment Module  
PM120, LI122, or LI122BL Room Controller

### Optional Components

NC415AV or NC404TS Master Station